PRE-FLIGHT CHECKLIST FOR PERSONAL EQUIPMENT SECTION

- 1. Pre-Breathing Room (T,O, Minus 2:20):
 - a. Orderliness
 - Security
 - c. Utilities (Electricity Air Conditioning)
- 2. Ground Vehicle Check (T.O. Minue 2:20):
 - 🚁. Walk Around check
 - b. Starting
 - On Board: Spare Pack (1) Facepiece (1) D-2, 425 psi (2) Cushions (2) Parachutes (2).
- 3. Aircraft Oxygen Check (T.O. Minus 2:20):
 - A. Position Seat Pack in cockpit
 - Oxygen pressure 1800 to 2000 psi

 - d. Check radio through seat pack
 - e. Check face piece heat on normal and by-pass
 - Arrange placement of seat belt, harness, seat pack leads
- 4. Pre-Breathing (T.O. Minus 2:00):
 - ✓a. Oxygen manifold and reduction system "ON"
 - b. 150 psi connected to console
 - c. Console check flow and pressure 2 to 3 mm Hg
 - ._d. Fit underwear to pilot
 - e. Check and fit helmet assembly to pilot
 - of. Connect face piece to console turn "ON"
 - g. Pre-breath pilot and note time "ON"
- 5. Check Personal Equipment:
- . . a. Suit condition
- b. Helmet
- c. Gloves

Approved For Release 2000/04/18: CIA-RDP89B00551R000100180011-9

- d. Boots
 - Le. Parachute
 - f. Coveralls
 - Vg. Face piece and carrier
 - ...h. Store items in sequence of wear after check.
 - i, Periodically insure pilot's oxygen supply adequacy and comfort
- 6. Clothing Pilot (T.O. Minue:30):
- ✓a. Fit Pilot's suit assembly plus coveralls. Check all zippers, lacings and general appearance.
 - b, Drinking water
- Remove pilot from console (Time noted); connect to D-2 charged 425 psi
 - . A. Escort pilot to vehicle and plane
 - 7. At Aircraft (T.O. Minus:20):
 - a. Fit parachute and back pack to pilot
 - 6. General evaluation of all garments
- Pilot hook-up in aircraft: Seat pack hook-up; engage capstan and breathing supply hoses; engage flight face piece to "T" block; connect amphenol; connect "U" plug; oxygen "ON"; check flow and change face piece; shoulder harness and seat belt; face piece heat check; press to test and check inflation.

 - Technician and vehicle remain "on line" until aircraft departure.

8. Post Flight:

- -a. Report to aircraft at "Switch Off" time.
- -b. Assist pilot out of aircraft and remove headgear.
- co- Remove personal equipment from cockpit.
- 2d. Return pilot to operations.
- Assist in removing clothing.
- clean and perform minute inspection of all equipment.
- 28. Report to de-briefing for pilot report.

25X1A 4/55^T

Enclosure 2 to SOP-O-1, Page 2